

**ImageMaster™**  
desktop card printers

## ImageMaster S-18



### *The Latest Generation of High-Speed Plastic Card Printing High-volume desktop printer with IP connectivity*

The fastest high-quality printer on the market today, the ImageMaster S-18 monochrome thermal printer allows you to personalize cards for customers, clients and employees, with outstanding speed and reliability.

Depending on card layout, the single-sided S-18 prints up to 1800 cards per hour. Designed to produce large quantities of cards reliably, consistently and without problems, ImageMaster S-18 printers are ideal for membership, loyalty and telephone card applications in bureau, gaming and leisure environments.

ImageMaster S-18 printers offer many unique capabilities and options. They deliver cost-saving features such as the ability to automatically use the minimum amount of ribbon needed to personalize a card. Compatible with a variety of card thicknesses and types, these printers boast the optional ability to handle clear cards, encode magnetic stripe cards and personalize smart cards. The printers feature a sophisticated cleaning system to

maintain a high printing standard, and add-ons include a carousel for multiple card types. A full range of different colour ribbons is supplied by NBS, and cost-saving narrow ribbons are also available.

ImageMaster S-18 printers support IP/Ethernet connectivity. By eliminating the need for print servers and interface boxes, the printers provide an extremely low cost of ownership. The S-18 comes standard with Windows XP driver for easy interface with many commercially available applications. NBS SmartSys Tabletop software is powerful available option. This user-friendly Windows® application offers powerful card design tools and compatibility with a wide variety of data sources which is ideal for batch issuance. The S-18 is also supplied with a keyboard for use, if required, in stand-alone mode.

#### FEATURES

- Delivers fast monochrome printing - up to 1800 single-sided
- Automatic card cleaning to help maintain quality
- Operates as a stand-alone unit with keyboard
- Supports IP & Ethernet connectivity
- 200-card auto-feed input hopper & auto-unload stacker
- Options for magnetic encoding & smart card personalization
- Carousel & clear card kit options available



**... speed & quality  
for a price  
that fits ...**



# ImageMaster™ S-18

## Technical Specifications

### GENERAL SPECIFICATIONS

- Fast, monochrome printing—up to 1800 single-sided cards depending on card layout
- 300 dots per inch (11.8 dots per mm) resolution
- Supports both internally generated layouts using ASCII text fields from host computer, or full Microsoft Windows® compatibility with Windows XP and Windows 2000 drivers
- Keyboard for manual data entry
- Supplied with Windows XP driver
- Two-line, 40-character LCD
- Password protection in operator and supervisor modes
- Auto-feed input hopper (200-card capacity)
- Auto-unload stacker (200-card capacity)
- Two production counters, one re-settable
- Automatic card cleaning mechanism with user configurable cleaning interval
- Reject tray (25 card capacity)
- Host computer communication interfaces: RS-232C Serial 9 Pin; Ethernet 10/100bT
- TCP/IP printing using LPR/LPD or Raw socket.
- Supports online printing from a variety of host computers including PC running Microsoft Windows XP, AS-400, and Linux/Unix systems
- Generates the following bar codes in layout mode:
  - > EAN 13 & 8, UPC-A, Code 39, Codabar, Code 128, Code 2 of 5
- Shipped with the following default fonts for layout mode:
  - > Swiss Regular: 6, 8, 10, 14, 18, 24 pt
  - > Swiss Italics: 6, 8, 10, 14 pt
  - > OCRA: 10, 12 pt
  - > Dutch Bold: 6, 8, 10, 18, 24 pt
  - > Any True-Type font can be downloaded from Microsoft Windows to support customized fonts
- PC Dash Board software for use in downloading additional fonts and images also used for flash loading of firmware for easy updates. It also can be used to back the machine settings.
- Ability to run the machine via telnet to allow for remote trouble-shooting and machine configuration
- Full range of monochrome colour ribbons (full and half widths) available
- RoHS Compliant

### OPTIONAL FEATURES

- Magnetic encoding: 3 track, Dual Coercivity, ISO 7811, Bit to Bit (binary), Bally's
- Smart Card ISO 7816 personalization
- Mifare Contactless Card Support
- Carousel: 6 input hoppers, each containing 100 cards 0.030" (0.76 mm) cards only
- Clear card kit
- Thin card kit for for 0.015" (0.38mm) and 0.020" (0.51 mm) cards

### CARD SPECIFICATIONS

- Types: PVC & composite PVC - including breakaway and key cards
- Maximum print area: 0.100" +/- 0.010" from side edges of card; 0.100" +/- 0.015" from top and bottom edges of card
- Card width/length: ISO 7810 (CR-80) 2.125" (54 mm) x 3.375" (86 mm)
- Card thickness: 0.024" (0.61 mm) to 0.030" (0.76mm)

### PHYSICAL DIMENSIONS


- Depth: 14.0" (356 mm)
- Width: 19.0" (482 mm)
- Height: 12" (305 mm)
- Weight: 52 lbs (23.6 kg)

### ELECTRICAL

- Power requirements: 110-230 Volts, 50-60 Hz
- FCC Class B, CE and ETL approved

### ENVIRONMENTAL

- Operating temperature: 15°C to 30°C
- Relative humidity: 20% to 65% non-condensing
- Storage temperature: -5°C to 70°C
- Storage humidity: 20% to 70% non-condensing
- Ventilation: Free air



- 1 - LCD Display
- 2 - Switch Panel
- 3 - Reject Tray
- 4 - Printhead
- 5 - Output Hopper
- 6 - Printing Foil
- 7 - Cleaning Tape
- 8 - Input Hopper



Optional 6-hopper carousel



Website: [www.nbstech.com](http://www.nbstech.com)  
Email: [info@nbstech.com](mailto:info@nbstech.com)

Corporate Headquarters  
Canada  
703 Evans Avenue  
Toronto, Ontario  
M9C 5E9  
Canada  
tel: +1 416.621.1911  
fax: +1 416.621.8875

Contact our NBS card personalization experts for full details on this and other card personalization products at:

Europe, Middle East, Africa  
B1 Moorfield Point  
Slyfield Industrial Park  
Guildford, Surrey GU1 1RU  
United Kingdom  
tel: +44 (0)1483 563200  
fax: +44 (0)1483 511189

North / South America  
10925 Bren Road E  
Minneapolis, MN 55343  
USA  
tel: +1 416.840.8620  
fax: +1 952.912.9439

Asia Pacific  
PO Box 780  
Hurstville BC  
NSW 1481  
Australia  
tel: +61 (2) 9546 6841  
fax: +61 (2) 9546 6851

©Feb 2009 NBS Technologies Inc. Specifications are subject to change without notice. All rights reserved. NBS and the NBS logo are registered trademarks of NBS Technologies Inc. in the United States and Canada and are trademarks in other countries. ImageMaster & SmartSys are trademarks of NBS Technologies Inc.